



*Technical Data Sheet*  
**6100 Stucco Recover**  
Epoxy Acrylic Hybrid Stucco Primer

### Product Description

Stucco Recover Epoxy Acrylic Primer from SRK Coatings, a semitransparent primer with excellent adhesion and with extremely high resistance to alkalinity, water, and efflorescence, is formulated for use on stucco and masonry walls. Stucco Recover Epoxy Acrylic Primer is a breathable coating that will effectively neutralize the substrate, block any water intrusion, and give a uniform, non porous substrate that will protect the final coat of paint from the effects of high alkalinity, thus stopping burn out and efflorescence. Stucco Recover Epoxy Acrylic Primer is supplied in a semitransparent yellow color (Tracer Yellow) to facilitate the monitoring of the priming progress.

### Performance Features

- Breathable
- Controls efflorescence, color burnout, cracks
- Water repellent

### Product Specifications

Resin Type:	Epoxy Acrylic Hybrid
Color Range:	Tracer Yellow
Finish:	Flat
Drying Time:	To touch: 30-60 minutes For topcoat: 2 hours or more
Practical Coverage:	150 sf/gal on coarse stucco 300 sf/gal on smooth stucco
Weight per gallon:	8.63 lbs.
Shelf Life:	2 years (unopened container) <90°
Size:	5 Gallon, Drum, Tote
VOC:	<.84 lbs/gal and <100.10 grams/liter
Cleanup:	Water
Solids by weight:	28.70%
Solids by volume:	28.38%

### Surface Preparation

Surface to be primed must be clean, free from all dirt, dust, grease, wax, and bleeding stains. All putty and caulk must be fully cured before priming.

### Application

Protect all non-stucco surfaces (glass, frames, aluminum, concrete, brick, wood, etc.) prior to spraying. Failure to protect these areas may result in staining.

Stucco Recover Epoxy Acrylic Primer should be applied with airless spray equipment set at the lowest pressure possible, using a 517 or 519 tip. Stucco Recover Epoxy Acrylic Primer should be applied at the rate of 150 square feet per gallon on coarse stucco, and 300 square feet per gallon on smooth stucco and concrete tilt walls. Top coats can be applied to this primer within two hours after priming. Clean equipment with water immediately after use.

### Top Coat

Top coats can be applied to the surface two hours after applying Stucco Recover. We suggest that you backroll the top coat using a water repellent 100% acrylic paint.

### Thinning

No thinning is required, and it is not recommended, but Stucco Recover may be thinned with up to one gallon of clean tap water per five gallons of primer.

### CAUTIONS

Do not apply when temperature is below 50 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

