



3000 Classic Series

Interior/Exterior Flat, Semi Gloss, & Primer

Product Description

Classic, a high-hiding, washable vinyl acrylic paint and primer, is designed for the professional painter where easy application and easy touch-ups are desired. Classic Flat is appropriate for interior or exterior surfaces, while Classic Semi Gloss is ideal for interior drywall and trim. Classic Primer may be used on interior drywall, plaster, brick, block and concrete. Classic is available in a wide variety of whites to pastel tones.

Performance Features

- High hiding
- Easy touchups
- Water Cleanup

Product Specifications

Resin Type:	VAE
Color Range:	White, pastels
Finish:	Flat or Semi Gloss
Drying Time:	To touch: 15-30 minutes To recoat: 1 hour up to 4 hours for semi gloss
Practical coverage:	Paint Up to 400 sq ft/gallon Primer Up to 250 sq ft/gallon
Weight per gallon:	Flat 12.18 lbs. Semi Gloss 10.20 lbs. Primer 11.01 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	Gallon, 5 Gallon
VOC	Flat <.14 lbs/gal / <16.91 g/liter Semi Gloss <.87 lbs/gal / <104.09 g/liter Primer <.74 lbs/gal / <87.69 g/liter
Cleanup:	Water
Solids by weight:	Flat 44.64% Semi Gloss 44.67% Primer 57.37%
Solids by volume:	Flat 26.92% Semi Gloss 32.46% Primer 38.21%

Surface Preparation

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

General:

Classic Flat may be used on brick, block, concrete, plaster, and drywall. Classic Semi Gloss is an ideal finish for interior surfaces, including kitchen and bathroom walls, baseboards, and door jambs. Surfaces to be painted with Classic must be clean, sound, and properly sealed.

Interior: Classic may be used as its own undercoater on drywall or plaster, or Classic Primer may be used. New walls must be properly sanded, dusted, and/or mopped before applying the primer or the first coat of Classic.

Exterior: Stucco and block surfaces must be tight and free from all chalk, dirt, and efflorescence. Chalky surfaces must be thoroughly cleaned by scrubbing with warm soapy water, and be rinsed well, or pressure washed. Remove all loose, scaling paint with a wire brush, a sandblaster, or a water blaster.

Application

Classic paint will cover up to 400 square feet per gallon depending upon the texture and porosity of the surface being painted, and the color being applied. Classic Primer will cover approximately 150-250 square feet per gallon. Classic may be applied with a brush, roller, or spray equipment. Clean equipment with water immediately after use.

Thinning

Classic may be thinned to the working consistency you desire with the addition of small amounts of clean tap water.

CAUTIONS

Do not apply when temperature is below 50 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.