



2300 Elite Flat

(formerly Classic Walls)
Interior Flat Paint

Product Description

Elite Flat is a high quality flat paint that can be successfully used on both interior and exterior surfaces. Smooth interior walls with drywall faults or with areas needing frequent touch ups are excellent candidates for Elite Flat. Touch ups are virtually invisible after the final coat of paint has dried. And what's more, Elite Flat on interior walls will withstand as much scrubbing as you can give it! Exterior stucco or block walls will also give years of service after being painted with Elite Flat. And lastly, Elite Flat is available in an unlimited array of colors from off-whites to medium shades to dark, rich hues.

Performance Features

- Invisible touch-ups
- Scrubbable
- Water Cleanup

Product Specifications

Resin Type:	VAE
Color Range:	Tintable White, Deep, X-Bases
Finish:	Flat
Drying Time:	To touch: 15-30 minutes To recoat: 1-2 hours
Practical coverage:	Up to 400 sq ft/gal
Weight per gallon:	12.00 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	Quart, Gallon, 5 Gallon
VOC	<.56 lbs/gal and <66.22 grams/liter
Cleanup:	Water
Solids by weight:	54.82%
Solids by volume:	35.68%

Surface Preparation

General

Elite Flat may be used on interior drywall or plaster walls, and exterior stucco or block. Do not use on unprimed wood. Surfaces to be painted with Elite Flat must be clean, sound, and properly sealed.

Interior: Elite Flat may be used as its own undercoater on drywall or plaster, or a good acrylic wall sealer may be used. New walls must be properly sanded, dusted, and/or mopped before applying the sealer or the first coat of Elite Flat.

Exterior: Stucco and block surfaces must be tight and free from all chalk, dirt, and efflorescence.

Application

Elite Flat may be applied with a brush, roller, or airless spray equipment. Clean equipment with water immediately after use.

Thinning

Small amounts of clean tap water may be used to thin to the desired working consistency.

CAUTIONS

Do not apply when temperature is below 50 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.