



# 2000 Elite

## 100% Acrylic Interior/Exterior Semi Gloss Wall Paint

### Product Description

Elite Semi Gloss is the ideal water reduced 100 % Acrylic enamel for interior or exterior walls, woodwork, and trim. Ideal for residential and commercial application.

### Performance Features

- Water Resistant
- Tough, durable finish
- Scrubbable
- Low Odor
- Water Cleanup

### Product Specifications

Resin Type:	Vinyl Acrylic
Color Range:	White, pastels to deep tints
Finish:	Semi Gloss 45-50°
Drying Time:	To touch: 30-45 minutes To recoat: 12 hours
Practical coverage:	Up to 400 sq ft/gallon
Recommended Dry film Thickness:	4.3 mils wet per coat 1.5 mils dry per coat
Weight per gallon:	10.031 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	Quart, Gallon, 5 Gallon
VOC	<1.02 lbs/gal and <121.18 grams/liter
Cleanup:	Water
Solids by weight:	46.36%
Solids by volume:	34.36%

### Surface Preparation

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### General:

Surface to be painted must be clean, free from all dirt, dust, grease, wax, and bleeding stains. When painting over an existing paint remove all loose, scaling paint with a wire brush, a sandblaster, or a water blaster. Chalky surfaces must be thoroughly cleaned by scrubbing with warm soapy water, and be rinsed well.

### Recommendations

Elite can be used successfully on metal, wood, cement, concrete block, drywall, or plaster. Different substrates require specific pretreatments, and/or primer. Please consult with your SRK supplier to help you determine the correct surface pretreatment and the appropriate primer for your specific application.

### Application

Elite may be applied with brush, roller, or spray equipment. Maintain a wet edge to avoid lap marks. Clean equipment with water immediately after use.

### Thinning

Elite may be thinned to the working consistency you desire with the addition of small amounts of clean tap water.

### CAUTIONS

Do not apply when temperature is below 50 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.