



6400 Reflex

Styrene Acrylic Elastomeric Roof Coating

Product Description

Reflex from SRK Coatings is a high solids elastomeric styrene acrylic coating specifically designed to coat previously coated roofs. The resin in Reflex is inherently flexible and retains its flexibility and toughness over long periods of time, and over wide ranges of temperatures. Reflex, formulated with minimum flow characteristics, clings to even the highest peaks of the substrate, ensuring full and uniform protection of the roof. Reflex is available in pure white. Reflex contains no lead or mercury, and with less than one half pound of VOCs per gallon, is an environmentally-friendly product.

Performance Features

- Flexible, yet tough
- Environmentally-friendly
- Economical

Product Specifications

Resin Type:	Styrene Acrylic
Color Range:	White
Finish:	Flat
Drying Time:	To touch: 1-2 hours To recoat: 24 hours
Practical coverage:	80 sq ft/gallon
Weight per gallon:	11.82 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	1 Gallon, 5 Gallon
VOC	<.47 lbs/gal / <55.41 g/liter
Cleanup:	Water
Solids by weight:	59.80%
Solids by volume:	47.54%

Surface Preparation

Reflex is to be used on urethane foam roofs. Surfaces to be coated with Reflex must be sound, clean, completely cured, chalk free, and dry.

To be used for Recoats only: Repair all damaged areas using VIP Textured Buttering Grade or other materials. Thoroughly clean the roof by scrubbing with a stiff bristle broom, and rinse well with clean tap water. Allow the surface to dry completely before proceeding.

Application

Reflex may be applied with a roller or with spray equipment using a Graco pump GH433 or larger with a .031 tip. To accomplish the functions of waterproofing, UV protection, and flexibility, it is essential that Reflex be applied at a spread rate which will yield a final film of no less than 20 mils. This can be accomplished by applying two coats of Reflex at the rate of 80 square feet per gallon per coat. Clean equipment with water immediately after use.

Thinning

No thinning is required or recommended.

CAUTIONS

Do not apply when temperature is below 55 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.

WARNING: If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.