



# 1600 SatinSheen Plus

## Interior/Exterior Eggshell Paint

### Product Description

SatinSheen Plus, a tough, long-lasting 100% acrylic enamel paint, can be used on virtually any paintable surface, both indoors and out. It dries to a pleasant, soft satin finish, and is available in a nearly limitless array of colors, from the softest, most subtle pastels, to the deepest, richest hues. SatinSheen Plus will withstand repeated scrubbing and abuses on interior surfaces, and many years of exposure to the elements on exterior surfaces. And, finally, SatinSheen Plus is virtually odor-free and mess-free. You can be confident you're painting with the best when you use SatinSheen Plus!

### Performance Features

- Low luster finish
- For any paintable surface
- Scrubbable

### Product Specifications

Resin Type:	100% Acrylic
Color Range:	Tintable White, Deep, X-Bases
Finish:	Eggshell
Drying Time:	To touch: 30-45 minutes To recoat: 12 hours
Practical coverage:	Up to 400 sq ft/gal
Weight per gallon:	10.54 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	Quart, Gallon, 5 Gallon
VOC	< 1.05 lbs/gal and <125.34 grams/liter
Cleanup:	Water
Solids by weight:	48.48%
Solids by volume:	35.25%

### Surface Preparation

#### General

SatinSheen Plus can be used effectively on exterior masonry, wood or metal surfaces, and on interior masonry, drywall, paneled walls, doors and trim. Surfaces to be painted with SatinSheen Plus must be clean, and free from all dirt, dust, grease, wax, and bleeding stains.

**Unpainted:** Different substrates require a specific pretreatment and/or primer. Consult with your SRK Coatings supplier to determine the correct surface preparation.

**Repaint:** all surfaces to be painted must be clean and free of all dirt, dust, loose or flaking paint, grease, or any other foreign matter. Remove all loose, scaling paint with a wire brush, a sandblaster, or a water blaster. Chalky surfaces must be thoroughly cleaned by scrubbing with warm soapy water, and be rinsed well.

#### Application

SatinSheen Plus may be applied with a brush, roller, or airless spray equipment. Clean equipment with water immediately after use.

#### Thinning

SatinSheen Plus may be thinned with Small amounts of clean tap water to the desired working consistency.

### CAUTIONS

Do not apply when temperature is below 50 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).