



# 6200 Superlastic

## 100% Acrylic Elastomeric Roof Coating Primer

### Product Description

Superlastic Roof Coating forms a thick rubber-like elastic cover to protect, insulate, and preserve your roof. Superlastic, expanding and contracting with the roof, reflects heat which lowers temperatures on the roof and inside the building. The result is energy savings for you and for the environment.

### Performance Features

- Energy Star Rated
- Reduces energy costs
- High solids content

### Product Specifications

Resin Type:	100% Acrylic
Color Range:	<b>919</b> White <b>924</b> Desert Tan
Finish:	Flat
Drying Time:	2-6 hours
Practical coverage:	50-100 sq ft/gallon
Weight per gallon:	11.79 lbs.
Shelf Life:	2 years (unopened container) <90°
Sizes:	5 Gallon
VOC	<b>919</b> <.44 lbs/gal / <52.27 g/liter <b>924</b> <.31 lb/gal and <37.24 g/liter
Cleanup:	Water
Solids by weight:	<b>919</b> 64.19% <b>924</b> 65.41%
Solids by volume:	<b>919</b> 50.53% <b>924</b> 51.11%

### Surface Preparation

Superlastic is to be used on urethane foam roofs. Surfaces to be coated with Superlastic must be sound, clean, completely cured, chalk-free, and dry. Take necessary measures to eliminate ponding water around drains, etc.

### Application

Superlastic will cover approximately 50-100 square feet per gallon depending on the porosity of the surface. Apply with a 1 1/4" nap roller cover or airless spray. Spread uniformly, making sure all cracks and seams are well coated. Apply only when temperatures will be above 55 degrees for at least four hours after application. Do not apply when heavy dew is expected within 4-6 hours. Superlastic will dry in two to six hours depending on weather conditions.

### Thinning

No thinning is required or recommended.

### CAUTIONS

Do not apply when temperature is below 55 degrees F. Do not apply to any exterior surface when rain is expected within 24 hours. Keep from freezing. Keep all unused material in tightly closed containers. Keep away from children. Do not take internally.

**WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).